

static control made **Easy!**





www.simco-ion.co.uk/our-products/static-elimination/ionising-air-guns/top-gun


Top Gun Sidekick

Top Gun III

lonising air guns and nozzles neutralise static chrages on serveral materials and clean the surface using ionised compressed air. Neutralising the static chrages makes it easier to blow clean the surface and prevents dus and dirt particles from being reattracked. The compressed air used for this purpose must be free from oil and water. The guns and nozzles are connected to a power unit which supplies the required high voltage. Simco-Ion's Top Gun III is developed for light industrial applications. A high ion production attewnd to an optimal neutralisation of static charges. High blow-off force and low air consumption provide high-efficincy cleaning. A filter at the exit of the gun ensures that the air is clea. The gun body is lightweight and durable. It features a light-touch trigger, making it comfortable even for extended use. All functionality is built into the gun, including a flowcontrol valve, and a two-level LED which indicates if the gun is in "stand by" mode and if high voltage is currently active. Both the gun and cable are static dissipative. A hanger is provided for easy mounting. One gun can be connected to one power unit.

Top Gun Sidekick

The Top Gun Sidekick offers hands-free operation. A foot pedal controls
both ionisation and airflow. The Top Gun Sidekick includes a flexible
mount feature with a bracket for flexible positioning.



Product Specifications

Static elimination lonising air guns



	+ - + - + - + - + - + - + -	+	-	+
Simco-Ion Netherla	nds	-	+	
Postbus 71		+	÷.	+
Lochem, The Netherlands	NL-7240 AB	+	T.	+
Tel: +31 (0)573 288333		-	+	_
Fax: +31 (0)573 257319		+	-	+
general@simco-ion.nl		7	+	+
· - + - + - + - +	- + - + - + - + - + - +	-	+	
Technical specifi	cations	÷	-	+
Working distance	300 mm max.	+	+	+
Housing material	impact resistant plastic	1	+	+
Emitter pins	special alloy		+	-
Cable	static dissipative, 3 metre	1	÷	+
Weight	0,8 kg incl. 3 metres cable	+	-	+
Ambient temprature	0- 40°C	+	+	+
Use circumstances	light industrial		+	-
Operating voltage	5 kV AC	÷	+	+
Noise level	76 dB using 2 bar at 0,6 m	÷	-	+
Air consumption	86 l/min. using 2 bar	+	+	+
Max. pressure	7 bar	-	+	-
Airconnection	1/8"NPT female	1	+	+
Airfilter	0,01 micron	+	-	+
Suitable power unit	Top Gung III power unit	+	+	+
	88 _ 34	-	+	-
		+	-	÷
<u> </u>		7	+	-
		+	÷	+
		+	_	+
		_	-	_

IIINNNN

Technical drawing Top Gun